

C l a i m s

1. An arrangement at a plug for sealing of liquid- or gas-carrying pipes, comprising a main section (1) having one or more axially arranged hydraulic cylinders (5),
5 fastening devices (13, 17, 21) and sealing surfaces (3, 23), c h a r a c t e r i z e d i n that the piston rod (9) of the hydraulic cylinder (5) is through-going.
2. An arrangement in accordance with Claim 1,
10 c h a r a c t e r i z e d i n that the ends (11, 15) of the piston rod are provided with ball joints (27).
3. An arrangement in accordance with one or more of the preceding claims, c h a r a c t e r i z e d i n
15 that predominantly axial bores for the passage of cables, liquid and gas are provided in the piston rod (9).
4. A method of fastening a plug for sealing of liquid- or gas-carrying pipes, comprising at least two
20 interconnected main sections (1) having one or more axially positioned hydraulic cylinders (5), fastening devices (13, 17, 21) and sealing surfaces (3, 23),
c h a r a c t e r i z e d i n that any one of the main sections (1) is fastened first by the hydraulic
25 cylinder (5) moving the second end plate (13) of the main section (1), so that the second end plate forces the slips (17) out over the conical force ring (21)

until the slips (17) are forced against the pipe wall (25) and the main section is locked in the pipe, and by the first end plate (3) simultaneously being moved towards the gasket (23), so that the gasket (23) and the first end plate (3) seal the pipe, and that any of the non-fastened main sections (1) is then fastened in the same manner, wherein the sequence of fastening of the main sections (1) is arbitrary.